

Revision nr. 5 Dated 24/11/2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Product Name: SEPARATOR FOR GINGIFAST

Code: C400888, C203227, C203232, C401500, C401520 **1.2. Relevant identified uses of the substance or mixture and uses advised against**

For professional use only. Isolator between two surfaces.

1.3. Details of the supplier of the safety data sheet

Name

Zhermack S.p.a

Via Bovazecchino 100

45021 Badia Polesine (RO)

Italy

tel. +39 0425-597611

fax +39 0425-597689

Competent person responsible for the safety data sheet:

msds@zhermack.com

1.4. Emergency telephone number

UK Emergency number: 999 (24 hours)


SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)



Danger, Flam. Lig. 2, Highly flammable liquid and vapour.



Warning, STOT SE 3, May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves and eye/face protection.

Revision nr. 5 Page n. 1 of 11



P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER if you feel unwell.

Special Provisions:

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains

ethyl acetate

Special provisions according to Annex XVII of REACH and subsequent amendments:

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

Not Applicable

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
>= 80% - < 90%	ethyl acetate	Index 607-022-00-5 number: CAS: 141-78-6 EC: 205-500-4 REACH No.: 01-21194751 03-46-XXXX	① 3.8/3 STOT SE 3 H336 ② 2.6/2 Flam. Liq. 2 H225 ① 3.3/2 Eye Irrit. 2 H319 EUH066

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap. Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediatley and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

Revision nr. 5 Page n. 2 of 11



SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

For emergency responders:

Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

7.2. Conditions for safe storage, including any incompatibilities

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

See section 10.5.

Instructions as regards storage premises:

Revision nr. 5 Page n. 3 of 11



Cool and adequately ventilated.

7.3. Specific end use(s) See section 1.2.

SECTION 8: Exposure controls/personal protection 8.1. Control parameters

SEPARATOR FOR GINGIFAST ethyl acetate - CAS: 141-78-6

OEL Type	TWA		Duratio	STEL		Duratio	Notes	Country
			n			n		
MAK	750	200	8h	1500	400	15min		GERMANY
	mg/m3	ppm		mg/m3	ppm			
AGW	730	200	8h	1460	400	15min		GERMANY
	mg/m3	ppm		mg/m3	ppm			
MAK	730	200	8h	1460	400	15min		SWITZERLA
	mg/m3	ppm		mg/m3	ppm			ND
AK	1400		8h	1400		15min		HUNGARY
	mg/m3			mg/m3				
HTP	730	200	8h	1470	400	15min		FINLAND
	mg/m3	ppm		mg/m3	ppm			
MAK	734	200	8h	1468	400	15min		AUSTRIA
	mg/m3	ppm		mg/m3	ppm			
NDS/NDSCh	200		8h	600		15min		POLAND
	mg/m3			mg/m3				
NGV/KGV	550	150	8h	1100	300	15min		SWEDEN
	mg/m3	ppm		mg/m3	ppm			
OELV		200	8h		400	15min		IRELAND
		ppm			ppm			
VLEP	734	200	8h	1468	400	15min		ITALY
	mg/m3	ppm		mg/m3	ppm			
RV	200	54 ppm	8h	1468	400	15min		LATVIA
	mg/m3			mg/m3	ppm			
TLV	400	111	8h	500	139	15min		ROMANIA
	mg/m3	ppm		mg/m3	ppm			
TLV	540	150	8h	1080	300	15min		DENMARK
	mg/m3	ppm		mg/m3	ppm			
VLEP	734	200	8h	1468	400	15min		FRANCE
	mg/m3	ppm		mg/m3	ppm			
VLEP	734	200	8h	1468	400	15min		BELGIUM
	mg/m3	ppm		mg/m3	ppm			
WEL	730	200	8h	1460	400	15min		UNITED
	mg/m3	ppm		mg/m3	ppm			KINGDOM
VLA	1460	400	8h					SPAIN
	mg/m3	ppm						
EU	734	200	8h	1468	400			
	mg/m3	ppm		mg/m3	ppm			
TLV-ACGIH		400	8h				URT and	
		ppm					eye irr	
ACGIH		400	8h				URT and	
		ppm					eye irr	

DNEL Exposure Limit Values ethyl acetate - CAS: 141-78-6



Worker Professional: 1468 mg/m3 - Exposure: Human Inhalation - Frequency: Short

Term, local effects

Worker Professional: 734 mg/m3 - Exposure: Human Inhalation - Frequency: Long

Term, local effects

Worker Professional: 1468 mg/m3 - Exposure: Human Inhalation - Frequency: Short

Term, systemic effects

Worker Professional: 734 mg/m3 - Exposure: Human Inhalation - Frequency: Long

Term, systemic effects

Worker Professional: 63 mg/kg bw/d - Exposure: Human Dermal - Frequency: Long

Term, systemic effects

PNEC Exposure Limit Values

ethyl acetate - CAS: 141-78-6

Target: Fresh Water - Value: 0.26 mg/l Target: Marine water - Value: 0.026 mg/l Target: Soil (agricultural) - Value: 0.24 mg/kg

Target: Marine water sediments - Value: 0.125 mg/kg Target: Freshwater sediments - Value: 1.25 mg/kg

8.2. Exposure controls

Precautionary measures:

Give adequate ventilation to the premises where the product is stored and/or handled.

Eye protection:

Wear airtight protective goggles.

Protection for skin:

Wear professional overalls and safety footwear.

Protection for hands:

Suitable material:

NBR (nitrile rubber).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

Respiratory protection:

Mask with filter "A", brown colour

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered (e.g. TLV-TWA).

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Appearance and colour:	Liquid,opaque		
Odour:	Typical of solvent		
Odour threshold:	Not available		
pH:	Not Relevant		
Melting point / freezing point:	Not available		
Initial boiling point and boiling range:	76	ASTM D 1120	

Revision nr. 5 Page n. 5 of 11



Flash point:	-1 ° C	ASTM D93-19	
Evaporation rate:	Not available		
Solid/gas flammability:	Not Relevant		
Upper/lower flammability	Not available		
or explosive limits:			
Vapour pressure:	Not available		
Vapour density:	Not available		
Relative density:	0.93 g/cm3 (calculated)		
Solubility in water:	Insoluble		
Solubility in oil:	Not available		
Partition coefficient	Not available		
(n-octanol/water):			
Auto-ignition temperature:	Not available		
Decomposition	Not available		
temperature:			
Viscosity:	Not available		
Explosive properties:	Not available		
Oxidizing properties:	ng properties: Not available		

9.2. Other information

Properties Value		Method:	Notes
Miscibility:	Not available		
Fat Solubility:	Not available		
Conductivity:	Not available		
Substance Groups	Not available		
relevant properties			

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

10.4. Conditions to avoid

Heat, direct sunlight.

Avoid bunching of electrostatic charges.

Avoid all sources of ignition.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

flammable gases / vapors

acetic acid

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the product: SEPARATOR FOR GINGIFAST a) acute toxicity Not classified



b) skin corrosion/irritation Not classified

c) serious eye damage/irritation

The product is classified: Eye Irrit. 2 H319

d) respiratory or skin sensitisation

Not classified

e) germ cell mutagenicity Not classified

f) carcinogenicity

Not classified

g) reproductive toxicity Not classified

h) STOT-single exposure

The product is classified: STOT SE 3 H336

i) STOT-repeated exposure

Not classified

j) aspiration hazard Not classified

Toxicological information of the main substances found in the product:

ethyl acetate - CAS: 141-78-6

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 4934 mg/kg - Source: (OECD 401, MSDS supplier).

Test: LD50 - Route: Skin - Species: Rabbit > 18000 mg/kg - Source: (MSDS supplier). Test: LC50 - Route: Inhalation - Species: Rat 56 mg/l - Duration: 4h - Source: (SDS supplier).

b) skin corrosion/irritation:

Species: Rabbit - Based on available data, the classification criteria are not met - Source: (OECD TG 404, MSDS supplier).

c) serious eye damage/irritation:

Species: Rabbit - Based on available data, the classification criteria are not met - Source: (OECD TG 405, MSDS supplier).

d) respiratory or skin sensitisation:

Species: Guinea pig - Based on available data, the classification criteria are not met - Source: (OECD TG 406, MSDS supplier).

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

SEPARATOR FOR GINGIFAST

Not classified for environmental hazards

Based on available data, the classification criteria are not met

ethyl acetate - CAS: 141-78-6

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish 230 mg/l - Duration h: 96h (Salmo gairdneri, MSDS supplier).

Endpoint: EC50 - Species: Daphnia 3090 mg/l - Duration h: 24h (Daphnia magna, DIN 38412, MSDS supplier).

Revision nr. 5 Page n. 7 of 11



Endpoint: EC50 - Species: Algae 3300 mg/l - Duration h: 48h (Scenedesmus

subspicatus, MSDS supplier).

Endpoint: NOEC - Species: Algae > 100 mg/l - Duration h: 72h (Desmodesmus

subspicatus, MSDS supplier).

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia 2.4 mg/l - Duration h: 21d (Daphnia magna, MSDS supplier).

12.2. Persistence and degradability

ethyl acetate - CAS: 141-78-6

Biodegradability: Readily biodegradable

12.3. Bioaccumulative potential

Not available

12.4. Mobility in soil

Not available

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information



14.1. UN number

ADR-UN Number: 1173 IATA-UN Number: 1173 IMDG-UN Number: 1173

14.2. UN proper shipping name

ADR-Shipping Name: ETHYL ACETATE IN MIXTURE IATA-Shipping Name: ETHYL ACETATE IN MIXTURE ETHYL ACETATE IN MIXTURE ETHYL ACETATE IN MIXTURE

14.3. Transport hazard class(es)

ADR-Class: 3
IATA-Class: 3
IATA-Label: 3
IMDG-Class: 3

14.4. Packing group

ADR-Packing Group: II IATA-Packing group: II IMDG-Packing group: II

14.5. Environmental hazards

ADR-Enviromental Pollutant: No IMDG-Marine pollutant: No

Revision nr. 5 Page n. 8 of 11



14.6. Special precautions for user

ADR-Subsidiary hazards: ADR-S.P.:

ADR-Transport category (Tunnel restriction code): 2 (D/E)

ADR - Hazard identification number: 33 IATA-Passenger Aircraft: 353 IATA-Subsidiary hazards: IATA-Cargo Aircraft: 364 IATA-S.P.: 3L IATA-ERG: IMDG-EmS: F-E,

S-D

IMDG-Subsidiary hazards:

IMDG-Stowage and handling: Category B

IMDG-Segregation:

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not Applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) 2015/830

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP) Regulation (EU) n. 2019/521 (ATP 12 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restriction 40

Restrictions related to the substances contained:

No restriction.

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Product belongs to category: P5c

Lagerklasse according to TRGS 510:

LGK 3: Flammable liquids

WGK Classification (Water hazard class - Verwaltungsvorschrift wassergefährdende Stoffe) WGK1 - Slightly hazardous for water

Revision nr. 5 Page n. 9 of 11



Lagerklasse according to TRGS 510:

LGK 3: Flammable liquids

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012: None.

California Proposition 65

Substance(s) listed under California Proposition 65:

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture. Substances for which a Chemical Safety Assessment has been carried out:

None

SECTION 16: Other information

Full text of phrases referred to in Section 3:

H336 May cause drowsiness or dizziness.

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

EUH066 Repeated exposure may cause skin dryness or cracking.

Hazard class and	Code	Description
hazard category		
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure,
		Category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Flam. Liq. 2, H225	On basis of test data
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H336	Calculation method

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECHA – European Chemical Agency

GESTIS - Information system on hazardous substances of the German Social Accident Insurance

IARC - International Agency for Research on Cancer

IPCS INCHEM – International Programme on Chemical Safety

ISS – Istituto Superiore di Sanità

PubChem - open chemistry database at the National Institutes of Health (NIH)

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Revision nr. 5 Page n. 10 of 11



ADR: European Agreement concerning the International Carriage of

Dangerous Goods by Road.

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

CAS: Chemical Abstracts Service (division of the American Chemical

Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of

Chemicals.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport

Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization"

(ICAO).

IMDG: International Maritime Code for Dangerous Goods.
INCI: International Nomenclature of Cosmetic Ingredients.

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

PNEC: Predicted No Effect Concentration.

RID: Regulation Concerning the International Transport of Dangerous Goods

by Rail.

STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWA: Time-weighted average
WGK: German Water Hazard Class.

Revision nr. 5 Page n. 11 of 11